

BC WIRE ROPE

Quality, No Compromise Since 1974



BC Wire Rope & Rigging is a full-service Rigging Loft incorporated in 1974. Our 'Quality, No compromise' philosophy has enabled us to grow throughout the many industries we serve. With corporate headquarters in Anaheim, CA, and branch locations in San Diego, CA, Tucson, AZ, Las Vegas, NV, and Elko, NV, BC Wire Rope & Rigging is committed to keeping our customers' jobs running smoothly. We do this by having in-house manufacturing, sufficient inventory, and a knowledgeable staff.

BC Wire Rope & Rigging is proud to offer the very best products in the industry. An authorized Distributor of Crosby, Bridon, and SlingMax products, we maintain a full inventory of products. We also provide products from other manufacturers depending on our customers' needs.

Bridon Dyform 34 MAX Wire Rope


Dyform 34 MAX is a high performance compacted low rotational rope that consists of varying multistrand rope designs which have undergone a final rope compacting process.

- Bridon Dyform 34MAX is the strongest of all ropes in the low rotation and rotation resistant product range - confirmed by Bridon's "Powercheck" testing of a sample from each production length.
- Greatest resistance to rotation of all ropes in the Rotation Resistant product range - confirmed by Bridon's unique "Twistcheck" type testing program.
- Superior bending fatigue life when compared with conventional Rotation Resistant ropes - confirmed by laboratory testing and extensive field experience.
- Excellent resistance to crushing and abrasion resulting from the overall compactness and robustness of the rope and the Dyform strands - recommended when multi-layer spooling is involved.
- Reduced elongation results from increased steel content and the Dyform process.
- Optional plastic coating of IWRC to further extend fatigue life, improve structural stability and resistance to corrosion.

Endurance Dyform® 34MAX

Diameter		Approx. mass WSC		Min. breaking force	
				Rope Grade	
				34MAX	
in	mm	lb/ft	kg/ft	tons	kN
1	26	2.26	0.99	76.9	684
	28	2.39	1.09	79.3	705
	30	2.76	1.25	91.6	814
1 1/4	32	3.15	1.43	105.0	933
		3.74	1.64	122.0	1085

NOTE: All sizes Powechecked



BRIDON

CALL BC WIRE ROPE