

BC WIRE ROPE

Quality, No Compromise Since 1974



BC Wire Rope & Rigging is a full-service Rigging Loft incorporated in 1974. Our 'Quality, No compromise' philosophy has enabled us to grow throughout the many industries we serve. With corporate headquarters in Anaheim, CA, and branch locations in San Diego, CA, Tucson, AZ, Las Vegas, NV, and Elko, NV, BC Wire Rope & Rigging is committed to keeping our customers' jobs running smoothly. We do this by having in-house manufacturing, sufficient inventory, and a knowledgeable staff.

BC Wire Rope & Rigging is proud to offer the very best products in the industry. An authorized Distributor of Crosby, Bridon, and SlingMax products, we maintain a full inventory of products. We also provide products from other manufacturers depending on our customers' needs.

Campbell Cam Alloy Chain

Cam-Alloy steel chain is electrically welded alloy steel embodying the latest manufacturing technology. Alloy provides a superior chain sling with high tensile strength and excellent wear resistance. The following chains meet or exceed all existing OSHA, ANSI, ASME, NACM and ASTM specification requirements. The Cam-Alloy chain and attachments used in fabricating Campbell chain slings offer a design factor of 4 to 1. System 8 is Campbell's trade name for Grade 80 chain. System 10 is Campbell's trade name for Grade 100 chain.



Trade Size	in.	mm	System	Nominal Dimensions (in. and mm)						Drum Cat. No.	UPC No. 020418	Working Load Limit		Feet/ Drum	Lb/ 100ft.	Links/ ft.
				Material Diameter		Inside Dimensions						lb	kg			
				in.	mm	Length		Width								
				in.	mm	in.	mm									
7/32	5.5	8		.22	6	.69	18	.30	8	0400312	063312	2100	970	800	43	17.5
9/32	7	10		.29	7	.86	22	.41	10	0405212	182204	4300	1950	500	74	13.8
3/8	10	10		.40	10	1.22	31	.55	14	0405412	182211	8800	3990	500	148	10.0
1/2	13	10		.52	13	1.57	40	.75	19	0405512	182228	15,000	6800	300	250	7.8
5/8	16	10		.64	16	1.93	49	.87	22	0405612	182235	22,600	10,250	200	379	6.5
3/4	20	10		.80	20	2.42	61	1.04	26	0405712	182242	35,300	16,000	100	610	4.9
7/8	22	10		.88	22	2.70	69	1.28	31	0405812	063497	42,700	19,400	100	775	4.4
1	26	8		1.00	25	2.80	71	1.40	36	0401612	063510	47,700	21,600	100	965	4.3
1 1/4	32	8		1.25	32	3.50	89	1.75	44	0402012	063534	72,300	32,800	60	1525	3.5

† Not to be used in the manufacture of chain slings

CALL BC WIRE ROPE